

베이커리 전용 냉동고는 소프트밀의 모든 기술력이 집약되어 첨단제상기능, 냉기내부순환 등 하이퀄리티 냉동고의 역할을 수행합니다.

## 급속냉동고 4도어(-35°C)

### -35°C 급속냉동

일본산부품과 명장 냉동기술을 적용하여 국내최고의 냉각성능을 발휘합니다. (초저온 스크롤 컴프레서 장착)



### 완벽한 냉기 차단

대형소프트밀만의 특수 가스켓을 적용해 밀폐력을 높이고 결로를 최소화 합니다.



## 급속냉동고 2도어

### LCD 컨트롤러

편리한 셋팅과 냉동보관 설정 등의 각종기능을 손쉽게 할 수 있습니다. (\*\*-35°C / \*-20°C)



### 강력한 대류냉각 시스템

대류팬 모터가 냉동고 내부 깊숙이 냉기를 순환시켜 안정적인 생산을 할 수 있습니다.



### 냉기순환식 내부구조

급속 냉기가 제품에 직접 닿지 않는 특화된 냉기순환식 내부구조로 설계되어 마르지 않고 제품 고유의 수분을 지켜 줍니다.

### 특수 경첩 적용

특수 경첩을 적용하여 밀폐력을 높이고, 분리가 가능하여 위생적으로 사용할 수 있습니다.



### 소프트밀 급냉시스템(SQC:Softmill Quick Composition)

• 급속냉동고와 냉동고를 같이 구성하여 급속냉동후의 보관까지 생각합니다.



▶ 급속냉동 · 냉동보관 ◀



▶ 급속냉동 · 냉동보관 ◀

모 델	SDHQ-28	SDHQ-18
규 격	1110(W) x 900(D) x 2030(H)	900(W) x 860(D) x 2030(H)
용 량	28매	18매
소비전력	380V, 3P, 3.5kW	380V, 3P, 3.5kW
설 치 시	배수관 (50A) 필요. 밀폐된 공간에 설치시 협의 필요. 배기 시설 필요	

This freezer is exclusively used for bakery. it is produced with all the technologies of SOFTMILL as a high-quality freezer with the functions of cutting-edge defrosting and cold air circulation.

## Quick Freezer 4 doors (-35°C)

### -35°C Quick Freezing

It has the best cooling performance in Korea as Japanese-made parts and master cooling technologies are used.  
(Equipped with a cryogenic scroll compressor)



### Perfect cold air blocking

As Daehung Softmill's special gaskets are used, it shows excellent airtightness, minimizing dew condensation.



## Quick Freezer 2 Doors

### LCD Controller

You can easily control various functions such as cold storage with convenient setting (\*\*-35°C / \*-20°C)



### Powerful Convection Cooling System

As a convection fan motor circulates cold air inside the freezer, you can produce products stably.



### Cold Air Circulation Internal Structure

A specialized cold air circulation structure is designed to prevent the cold air from touching the products directly, thus keeping the moisture of the product without getting dry.

### Use of special hinges

The use of special hinges enhances airtightness and makes it possible to detach them for hygienic use.



### SOFTMILL Quick Cooling System (SQC: Softmill Quick Composition)

• As a quick freezer and a freezer are combined together, you can store the products easily after quick cooling.



▶ Quick cooling · Cold storage ◀

▶ Quick cooling · Cold storage ◀

Model	SDHQ-28	SDHQ-18
Dimension	1110(W) × 1000(D) × 2030(H)	900(W) × 960(D) × 2030(H)
Capacity	28 trays	18 trays
Power consumption	380V, 3P, 3.5kW	380V, 3P, 3.5kW
At the time of installation	Drain pipe (50A) and exhaust facility are required. Consultation is required if it is installed in a sealed space.	